

MODEL
ECThe **INDUSTRY
LEADER -
STRENGTH and
DEPENDABILITY****EC Hook & Lug Suspension Models****1/4 - 5 Ton****Made in USA**

COFFING EC Models - High performance hoists engineered for heavy duty industrial service. Designed for safety, the EC incorporates mechanical load brake, motor brake, and overload clutch as standard.

CAPACITIES & LIFTS - Rated loads from 1/4 to 5 Tons, with 10, 15, and 20-foot standard lifts. Other lifts available. Standard push button drop is 4-feet less than lift.

VOLTAGE & MOTOR OPTIONS - 115/230, 208 - single phase; 230/460, 208, 220/380, 575 - three phase. 60 hertz standard, 50 hertz available. Two-speed motors available (3 to 1 speed ratio).

SUSPENSION OPTIONS - Rigid or swivel top hook, lug, plain, geared, and motorized trolley available.

STANDARD FEATURES - Refer to pages 8 & 9.

SMALL FRAME DESIGN - Features housings of cast aluminum alloy construction for minimum weight. Engineered and designed for use with motors up to 1 HP.

LARGE FRAME DESIGN - Features load bearing housings of ductile iron construction for maximum strength. Non-load bearing housings of cast aluminum alloy for minimum weight. Engineered and designed for use with higher torque 2 and 3 HP three phase motors.

DURABLE CONSTRUCTION - Built in compliance with ASME/ANSI B30.16 and CSA standards.

ACCESSORIES & OPTIONS - Full line of accessories available, including Variable Frequency Drives. See pages 25-31.

LIFETIME WARRANTY

COFFING®
HOISTS

● SPECIFICATIONS ●

EC Hook & Lug Suspension Models

Capacity			Model Number	Frame *	No. of Chains	Motor HP	Lift Speed (fpm)		Headroom (in.)	Housing Dimensions (in.)			Net Wt. ** (lb.)
(lb.)	(kg) †	(Ton)					Single	Two ††		H	W	L	
500	250	1/4	EC-0516	S	1	1/4	16	5.3	16 7/8	8	11 5/8	23 3/8	100
500	250	1/4	EC-0532	S	1	1/2	32	10.7	16 7/8	8	11 5/8	23 3/8	108
500	250	1/4	EC-0564	S	1	1	64	21.3	16 7/8	8	11 5/8	23 3/8	116
1000	500	1/2	EC-1009	S	1	1/4	9	3	16 7/8	8	11 5/8	23 3/8	104
1000	500	1/2	EC-1016	S	1	1/2	16	5.3	16 7/8	8	11 5/8	23 3/8	106
1000	500	1/2	EC-1032	S	1	1	32	10.7	16 7/8	8	11 5/8	23 3/8	118
2000	1000	1	EC-2004	S	2	1/4	4	1.3	18 1/4	8	11 5/8	23 3/8	116
2000	1000	1	EC-2008	S	2	1/2	8	2.7	18 1/4	8	11 5/8	23 3/8	116
2000	1000	1	EC-2012	S	1	1	12	4	16 7/8	8	11 5/8	23 3/8	114
2000	1000	1	EC-2016	S	1	1	16	5.3	16 7/8	8	11 5/8	23 3/8	118
2000	1000	1	EC-2032	L	1	2	32	10.7	23	10 7/8	14 13/16	31 3/16	295
2000	1000	1	EC-2048	L	1	3	48	16	23	10 7/8	14 13/16	31 3/16	302
4000	2000	2	EC-4006	S	2	1	6	2	18 15/16	8	11 5/8	23 3/8	127
4000	2000	2	EC-4008	S	2	1	8	2.7	18 15/16	8	11 5/8	23 3/8	133
4000	2000	2	EC-4016	L	1	2	16	5.3	23	10 7/8	14 13/16	31 3/16	295
4000	2000	2	EC-4024	L	1	3	24	8	23	10 7/8	14 13/16	31 3/16	302
6000		3	EC-6005	S	3	1	5	1.7	23 1/4	8	12	26 3/8	200
6000	3000	3	EC-6010	L	2	2	10	3.3	27 3/8	10 7/8	14 13/16	31 3/16	340
6000	3000	3	EC-6016	L	2	3	16	5.3	27 3/8	10 7/8	14 13/16	31 3/16	347
8000		4	EC-8008	L	2	2	8	2.7	27 3/8	10 7/8	14 13/16	31 3/16	345
8000		4	EC-8012	L	2	3	12	4	27 3/8	10 7/8	14 13/16	31 3/16	352
10000	5000	5	EC-10005	L	3	2	5	1.7	27 7/8	10 7/8	14 13/16	31 3/16	393
10000	5000	5	EC-10008	L	3	3	8	2.7	27 7/8	10 7/8	14 13/16	31 3/16	393

† Metric rated option available

* **S** = Small frame hoist, parallel mounted, single or three phase. **L** = Large frame hoist, cross mounted, three phase only.

** For 10 ft. lift, top hook suspension and lug suspension units.

Note: For complete dimensional data, refer to Coffing Dimensional Databook.





SUSPENSIONS for a VARIETY of APPLICATIONS

EC Trolley Suspensions

COFFING ECT, ECGT, and ECMT Models - Plain, geared and motorized trolley suspensions with all the features of basic EC models for added flexibility in a variety of applications.

PLAIN TROLLEY - For manual positioning of hoist and load.

GEARED TROLLEY - For more precise positioning of hoist and load. Standard hand chain drop is 2-feet less than lift.

MOTORIZED TROLLEY - For faster positioning of hoist and load over longer distances. 35 or 75 FPM speeds standard with optional speeds of 18, 24, 50, 100, and 150 FPM.

VOLTAGES - 115/230, 208 - single phase; 230/460, 208, 220/380, 575 - three phase. 60 hertz standard, 50 hertz available.

TWO-SPEED MOTORIZED TROLLEY MODELS - Optional with 3 to 1 speed ratio, three-phase, single voltage only.

WRAP-AROUND SIDE PLATES - Act as safety lugs and as bumpers to protect wheels. Available to fit American Standard I-Beams, wide-flange, and patented track beams. Specify track type and beam size.

PRECISION TROLLEY WHEELS - Machined, cast iron wheels with sealed, lifetime lubricated ball bearings for extended trolley life. Motorized trolley wheels heat treated for added durability. Bronze and stainless steel wheels optional.

TWO TROLLEY DESIGNS - 4-wheel design on 1/4 - 3 ton negotiates 48" minimum radius curve, including patented track applications. 8-wheel design on 4 and 5 ton reduces beam flange stress.

ACCESSORIES & OPTIONS - Full line available to meet a variety of applications. See pages 25-31.

LIFETIME WARRANTY



1/4 - 5 Ton

Made in USA

COFFING[®]
HOISTS



● SPECIFICATIONS ●

EC Plain, Geared & Motorized Suspensions

Capacity			Model Number	Frame * Size	Trolley † Mount	ECT & ECGT Hdrm (in.)	ECMT Hdrm (in.)	Flange Width (in.)	Min. Rad. Curve (in.)	Net Wt. ** (lb.)	ECMT Net Wt. (lb.)
(lb.)	(kg) ‡	(Ton)									
500	250	1/4	EC(†)-0516	S	P	17 1/4	17 1/4	3.332 - 7	48	145	180
500	250	1/4	EC(†)-0532	S	P	17 1/4	17 1/4	3.332 - 7	48	153	188
500	250	1/4	EC(†)-0564	S	P	17 1/4	17 1/4	3.332 - 7	48	161	196
1000	500	1/2	EC(†)-1009	S	P	17 1/4	17 1/4	3.332 - 7	48	151	186
1000	500	1/2	EC(†)-1016	S	P	17 1/4	17 1/4	3.332 - 7	48	151	186
1000	500	1/2	EC(†)-1032	S	P	17 1/4	17 1/4	3.332 - 7	48	163	198
2000	1000	1	EC(†)-2004	S	P	18 5/8	18 5/8	3.332 - 7	48	161	196
2000	1000	1	EC(†)-2008	S	P	18 5/8	18 5/8	3.332 - 7	48	161	196
2000	1000	1	EC(†)-2012	S	P	17 1/4	17 1/4	3.332 - 7	48	158	194
2000	1000	1	EC(†)-2016	S	P	17 1/4	17 1/4	3.332 - 7	48	163	198
2000	1000	1	EC(†)-2032	L	C	21 9/16	22 1/4	3.332 - 7	48	347	375
2000	1000	1	EC(†)-2048	L	C	21 9/16	22 1/4	3.332 - 7	48	347	375
4000	2000	2	EC(†)-4006	S	P	19 5/16	19 5/16	3.332 - 7	48	172	207
4000	2000	2	EC(†)-4008	S	P	19 5/16	19 5/16	3.332 - 7	48	178	213
4000	2000	2	EC(†)-4016	L	C	21 9/16	22 1/4	3.332 - 7	48	347	375
4000	2000	2	EC(†)-4024	L	C	21 9/16	22 1/4	3.332 - 7	48	354	362
6000		3	EC(†)-6005	S	P	23 1/4	24	3.332 - 7	48	260	320
6000	3000	3	EC(†)-6010	L	C	26	26 5/8	3.332 - 7	48	396	424
6000	3000	3	EC(†)-6016	L	C	26	26 5/8	3.332 - 7	48	403	431
8000		4	EC(†)-8008	L	C	25 15/16	26 3/4	4 - 7	***	520	560
8000		4	EC(†)-8012	L	C	25 15/16	26 3/4	4 - 7	***	527	567
10000	5000	5	EC(†)-10005	L	C	29 3/4	30 5/8	4 - 7	***	561	599
10000	5000	5	EC(†)-10008	L	C	29 3/4	30 5/8	4 - 7	***	568	606

† Specify **ECT** for plain trolley, **ECGT** for geared trolley and **ECMT** for motorized trolley models

‡ Metric rated option available

* **S** = Small frame hoist, parallel mounted, single or three phase.
L = Large frame hoist, cross mounted, three phase only.

†* **P** = Parallel mount, standard on small frame hoists.
C = Cross mount, standard on large frame hoists.

** Weight for 10 ft. lift ECT units. Add 10 lb. for ECGT unit weights.

*** 4 & 5 ton straight track only. Articulated model for 48" min. radius curved track available - consult factory.

Note: For complete dimensional data, refer to Coffing Dimensional Databook.

