



Reversed Eye (RE - TYPE VI)

Reversed Eye "RE" (return eye) slings are formed by using multiple widths of webbing held edge to edge. A wear pad is attached on both sides of the web sling body, and on both sides of the loop eyes to form a loop eye at each end, which is at a right angle to the plane of the web sling body. The Reversed Eye sling can be used with all three hitch types (vertical, basket, choker), but is particularly well suited to the choker hitch due to the "twisted eye".



REVERSED EYE CAPACITY CHART


Part Number	Sling Width (inches)	Rated Capacity (lbs.)			Eye Dimensions		
		Vertical	Choker	Vertical Basket	Width (inches)	Length (inches)	Min. Standard Length (ft)
RE192	2	4,600	3,680	9,200	1	9	3
RE292	2	7,700	6,160	15,400	1	12	3
RE193	3	6,900	5,520	13,800	1-1/2	12	4
RE293	3	11,600	9,280	23,200	1-1/2	12	4
RE194	4	8,600	6,880	17,200	1	12	4
RE294	4	14,500	11,600	29,000	2	18	6
RE394	4	20,400	16,320	40,800	2	18	6
RE494	4	23,000	18,400	46,000	2	18	6
RE196	6	12,000	9,600	24,000	1-1/2	14	6
RE296	6	17,400	13,920	34,800	1-1/2	18	6
RE396	6	26,500	21,200	53,000	3	20	6
RE496	6	34,000	27,200	68,000	3	24	6

*Before ordering slings that are going to be used in a chemically active environment, contact Liftex® Customer Service, to recommend the right sling for the right usage.

Chemically Active Environments can affect the strength of webbing slings in varying degrees, ranging from little to total degradation.

Available in:





WARNING

SLING FAILURE CAN CAUSE
DEATH OR INJURY

SLING FAILURE RESULTS FROM MISUSE, DAMAGE, AND EXCESSIVE WEAR

ADHERE TO INDUSTRY STANDARDS & REGULATIONS

HOW TO ORDER INSTRUCTIONS

